Package: robustmatrix (via r-universe)

October 20, 2026

Type Package

Title Robust Matrix-Variate Parameter Estimation

Version 0.1.5

Maintainer Marcus Mayrhofer <marcus.mayrhofer@tuwien.ac.at>

Description Robust covariance estimation for matrix-valued data and data with Kronecker-covariance structure using the Matrix Minimum Covariance Determinant (MMCD) estimators and outlier explanation using and Shapley values.

License GPL-3

Encoding UTF-8

LazyData true

LinkingTo Rcpp, RcppArmadillo, RcppProgress

Imports Rcpp, stats, Rdpack

Suggests knitr, rmarkdown, roxygen2, gridExtra, dplyr, forcats, ggnewscale, ggplot2, ggrepel, tibble, tidyr

RoxygenNote 7.3.3

RdMacros Rdpack

VignetteBuilder knitr

Depends R (>= 4.0.0)

NeedsCompilation yes

Author Marcus Mayrhofer [aut, cre], Una Radojičić [aut], Peter Filzmoser [aut]

Repository https://marcusmayrhofer.r-universe.dev

Date/Publication 2026-03-24 16:30:07 UTC

RemoteUrl https://github.com/cran/robustmatrix

RemoteRef HEAD

RemoteSha dcd30fd254320d254bab530bb09da2d934453dc1

Contents

clean_prob_mmcd . . . 2
cstep . . . 3
darwin . . . 5
matrixShapley . . . 6
mmcd . . . 7
mmd . . . 10
mmle . . . 11
n_subsets_mmcd . . . 13
rmatnorm . . . 14
weather . . . 15

Index **16**

`clean_prob_mmcd` *Probability of obtaining at least one clean h-subset in the* `mmcd` *function.*

Description

Probability of obtaining at least one clean h-subset in the `mmcd` function.

Usage

```
clean_prob_mmcd(p, q, n_subsets = 500, contamination = 0.5)
```

Arguments

`p`	number of rows.
`q`	number of columns.
`n_subsets`	number of elemental h-substs (default is 500).
`contamination`	level of contamination (default is 0.5).

Value

Probability of obtaining at least one clean h-subset in the `mmcd` function.

`cstep` *C-step of Matrix Minimum Covariance Determinant (MMCD) Estimator*

Description

This function is part of the FastMMCD algorithm (Mayrhofer et al. 2025).

Usage

```
cstep(
  X,
  alpha = 0.5,
  cov_row_init = NULL,
  cov_col_init = NULL,
  weight_mat_row = NULL,
  weight_mat_col = NULL,
  diag = "none",
  h_init = -1L,
  init = TRUE,
  max_iter = 100L,
  max_iter_MLE = 100L,
  lambda = 0,
  adapt_alpha = TRUE
)
```

Arguments

`X`	a 3d array of dimension (p, q, n), containing n matrix-variate samples of p rows and q columns in each slice.
`alpha`	numeric parameter between 0.5 (default) and 1. Controls the size $h \approx alpha * n$ of the h-subset over which the determinant is minimized.
`cov_row_init`	matrix. Initial `cov_row` $p \times p$ matrix, must be a positive definite symmetric matrix. Identity by default.
`cov_col_init`	matrix. Initial `cov_col` $p \times p$ matrix, must be a positive definite symmetric matrix. Identity by default.
`weight_mat_row`	$p \times p$ matrix. Weights applied to `cov_row` by elementwise multiplication, must be a positive definite symmetric matrix. `NULL` by default and not used.
`weight_mat_col`	$q \times q$ matrix. Weights applied to `cov_col` by elementwise multiplication, must be a positive definite symmetric matrix. `NULL` by default and not used.
`diag`	Character. If "none" (default) all entries of `cov_row` and `cov_col` are estimated. If either "both", "row", or "col" only the diagonal entries of the respective matrices are estimated.
`h_init`	Integer. Size of initial h-subset. If smaller than 0 (default) size is chosen automatically.

init	Logical. If TRUE (default) elemental subsets are used to initialize the procedure.
max_iter	upper limit of C-step iterations (default is 100)
max_iter_MLE	upper limit of MLE iterations (default is 100)
lambda	a smooting parameter for the rowwise and columnwise covariance matrices.
adapt_alpha	Logical. If TRUE (default) alpha is adapted to take the dimension of the data into account.

Value

A list containing the following:

mu	Estimated $p \times q$ mean matrix.
cov_row	Estimated p times p rowwise covariance matrix.
cov_col	Estimated q times q columnwise covariance matrix.
cov_row_inv	Inverse of cov_row.
cov_col_inv	Inverse of cov_col.
md	Squared Mahalanobis distances.
md_raw	Squared Mahalanobis distances based on *raw* MMCD estimators.
det	Value of objective function (determinant of Kronecker product of rowwise and columnwise covariane).
dets	Objective values for the final h-subsets.
h_subset	Final h-subset of *raw* MMCD estimators.
iterations	Number of C-steps.

See Also

mmcd

Examples

```
n = 1000; p = 2; q = 3
mu = matrix(rep(0, p*q), nrow = p, ncol = q)
cov_row = matrix(c(1,0.5,0.5,1), nrow = p, ncol = p)
cov_col = matrix(c(3,2,1,2,3,2,1,2,3), nrow = q, ncol = q)
X <- rmatnorm(n = 1000, mu, cov_row, cov_col)
ind <- sample(1:n, 0.3*n)
X[,,ind] <- rmatnorm(n = length(ind), matrix(rep(10, p*q), nrow = p, ncol = q), cov_row, cov_col)
par_mmle <- mmle(X)
par_cstep <- cstep(X)
distances_mmle <- mmd(X, par_mmle$mu, par_mmle$cov_row, par_mmle$cov_col)
distances_cstep <- mmd(X, par_cstep$mu, par_cstep$cov_row, par_cstep$cov_col)
plot(distances_mmle, distances_cstep)
abline(h = qchisq(0.99, p*q), lty = 2, col = "red")
abline(v = qchisq(0.99, p*q), lty = 2, col = "red")
```

`darwin` *DARWIN (Diagnosis AlzheimeR WIth haNdwriting)*

Description

The DARWIN (Diagnosis AlzheimeR WIth haNdwriting) dataset comprises handwriting samples from 174 individuals. Among them, 89 have been diagnosed with Alzheimer's disease (AD), while the remaining 85 are considered healthy subjects (H). Each participant completed 25 handwriting tasks on paper, and their pen movements were recorded using a graphic tablet. From the raw handwriting data, a set of 18 features was extracted.

Usage

```
data(darwin)
```

Format

An array of dimension (p, q, n), comprising $n = 174$ observations, each represented by a $p = 18$ times $q = 25$ dimensional matrix. The observed parameters are:

- Total Time
- Air Time
- Paper Time
- Mean Speed on paper
- Mean Acceleration on paper
- Mean Acceleration in air
- Mean Jerk on paper
- Pressure Mean
- Pressure Variance
- Generalization of the Mean Relative Tremor (GMRT) on paper
- GMTR in air
- Mean GMRT
- Pendowns Number
- Max X Extension
- Max Y Extension
- Dispersion Index

Source

UC Irvine Machine Learning Repository - DARWIN - doi:10.24432/C55D0K

References

Cilia ND, De Stefano C, Fontanella F, Di Freca AS (2018). "An experimental protocol to support cognitive impairment diagnosis by using handwriting analysis." *Procedia Computer Science*, **141**, 466–471.
Cilia ND, De Gregorio G, De Stefano C, Fontanella F, Marcelli A, Parziale A (2022). "Diagnosing Alzheimer's disease from on-line handwriting: a novel dataset and performance benchmarking." *Engineering Applications of Artificial Intelligence*, **111**, 104822.

`matrixShapley` *Outlier explanation based on Shapley values for matrix-variate data*

Description

`matrixShapley` decomposes the squared matrix Mahalanobis distance (`mmd`) into additive outlyingness contributions of the rows, columns, or cell of a matrix (Mayrhofer and Filzmoser 2023; Mayrhofer et al. 2025).

Usage

```
matrixShapley(X, mu = NULL, cov_row, cov_col, inverted = FALSE, type = "cell")
```

Arguments

`X`	a 3d array of dimension (p, q, n), containing n matrix-variate samples of p rows and q columns in each slice.
`mu`	a $p \times q$ matrix containing the means.
`cov_row`	a $p \times p$ positive-definite symmetric matrix specifying the rowwise covariance matrix
`cov_col`	a $q \times q$ positive-definite symmetric matrix specifying the columnwise covariance matrix
`inverted`	Logical. FALSE by default. If TRUE `cov_row` and `cov_col` are supposed to contain the inverted rowwise and columnwise covariance matrices, respectively.
`type`	Character. Either "row", "col", or "cell" (default) to compute rowwise, columnwise, or cellwise Shapley values.

Value

Rowwise, columnwise, or cellwise Shapley value(s).

References

Mayrhofer M, Filzmoser P (2023). "Multivariate outlier explanations using Shapley values and Mahalanobis distances." *Econometrics and Statistics*.

Mayrhofer M, Radojičić U, Filzmoser P (2025). "Robust covariance estimation and explainable outlier detection for matrix-valued data." *Technometrics*, 1–15.

See Also

mmd.

Examples

```
set.seed(123)
n = 1000; p = 2; q = 3
mu = matrix(rep(0, p*q), nrow = p, ncol = q)
cov_row = matrix(c(5,2,2,4), nrow = p, ncol = p)
cov_col = matrix(c(3,2,1,2,3,2,1,2,3), nrow = q, ncol = q)
X <- rmatnorm(n = 1000, mu, cov_row, cov_col)
X[1:2,1,1] <- c(-10, 10)
X[2,2,1] <- 20

# Cellwise Shapley values additively decompose the squared Mahalanobis distance
# into outlyingness contributions of each cell:
cellwise_shv <- matrixShapley(X, mu, cov_row, cov_col)
cellwise_shv[,,1]
distances <- mmd(X, mu, cov_row, cov_col)
# verify that sum of cellwise Shapley values is equal to squared MMDs:
all.equal(target = apply(cellwise_shv, 3, sum), current = distances)
# For plots and more details see vignette("MMCD_examples").
```

---

mmcd *The Matrix Minimum Covariance Determinant (MMCD) Estimator*

Description

mmcd computes the robust MMCD estimators of location and covariance for matrix-variate data using the FastMMCD algorithm (Mayrhofer et al. 2025).

Usage

```
mmcd(
  X,
  nsamp = 500L,
  alpha = 0.5,
  cov_row_init = NULL,
  cov_col_init = NULL,
  weight_mat_row = NULL,
  weight_mat_col = NULL,
  diag = "none",
  lambda = 0,
  max_iter_cstep = 100L,
  max_iter_MLE = 100L,
  max_iter_cstep_init = 2L,
  max_iter_MLE_init = 2L,
  nmini = 300L,
```

```
  nsub_pop = 1500L,
  adapt_alpha = TRUE,
  reweight = TRUE,
  scale_consistency = "quant",
  outlier_quant = 0.975,
  nthreads = 1L,
  display_progress = FALSE
)
```

Arguments

X	a 3d array of dimension (p, q, n), containing n matrix-variate samples of p rows and q columns in each slice.
nsamp	number of initial h-subsets (default is 500).
alpha	numeric parameter between 0.5 (default) and 1. Controls the size $h \approx alpha * n$ of the h-subset over which the determinant is minimized.
cov_row_init	matrix. Initial cov_row $p \times p$ matrix, must be a positive definite symmetric matrix. Identity by default.
cov_col_init	matrix. Initial cov_col $p \times p$ matrix, must be a positive definite symmetric matrix. Identity by default.
weight_mat_row	$p \times p$ matrix. Weights applied to cov_row by elementwise multiplication, must be a positive definite symmetric matrix. NULL by default and not used.
weight_mat_col	$q \times q$ matrix. Weights applied to cov_col by elementwise multiplication, must be a positive definite symmetric matrix. NULL by default and not used.
diag	Character. If "none" (default) all entries of cov_row and cov_col are estimated. If either "both", "row", or "col" only the diagonal entries of the respective matrices are estimated.
lambda	a smooting parameter for the rowwise and columnwise covariance matrices.
max_iter_cstep	upper limit of C-step iterations (default is 100)
max_iter_MLE	upper limit of MLE iterations (default is 100)
max_iter_cstep_init	upper limit of C-step iterations for initial h-subsets (default is 2)
max_iter_MLE_init	upper limit of MLE iterations for initial h-subsets (default is 2)
nmini	for $n > 2 * nmini$ the algorithm splits the data into smaller subsets with at least nmini samples for initialization (default is 300)
nsub_pop	for $n > 2 * nmini$ a subpopulation of $\min(n, nsub_pop)$ samples is divided into $k = floor(\min(n, nsub_pop)/nmini)$ subsets for initialization (default is 1500)
adapt_alpha	Logical. If TRUE (default) alpha is adapted to take the dimension of the data into account.
reweight	Logical. If TRUE (default) the reweighted MMCD estimators are computed.

`scale_consistency`
: Character. Either "quant" (default) or "mmd_med". If "quant", the consistency factor is chosen to achieve consistency under the matrix normal distribution. If "mmd_med", the consistency factor is chosen based on the Mahalanobis distances of the observations.

`outlier_quant`
: numeric parameter between 0 and 1. Chi-square quantile used in the reweighting step.

`nthreads`
: Integer. If 1 (default), all computations are carried out sequentially. If larger then 1, C-steps are carried out in parallel using `nthreads` threads. If < 0, all possible threads are used.

`display_progress`
: Logical. If TRUE, progress bars are shown. Default is FALSE.

Details

The MMCD estimators generalize the well-known Minimum Covariance Determinant (MCD) (Rousseeuw 1985; Rousseeuw and Driessen 1999) to the matrix-variate setting. It looks for the h observations, $h = \alpha * n$, whose covariance matrix has the smallest determinant. The FastMMCD algorithm is used for computation and is described in detail in (Mayrhofer et al. 2025). NOTE: The procedure depends on *random* initial subsets. Currently setting a seed is only possible if `nthreads = 1`.

Value

A list containing the following:

`mu`
: Estimated $p \times q$ mean matrix.

`cov_row`
: Estimated p times p rowwise covariance matrix.

`cov_col`
: Estimated q times q columnwise covariance matrix.

`cov_row_inv`
: Inverse of `cov_row`.

`cov_col_inv`
: Inverse of `cov_col`.

`md`
: Squared Mahalanobis distances.

`md_raw`
: Squared Mahalanobis distances based on *raw* MMCD estimators.

`det`
: Value of objective function (determinant of Kronecker product of rowwise and columnwise covariane).

`alpha`
: The (adjusted) value of alpha used to determine the size of the h-subset.

`consistency_factors`
: Consistency factors for raw and reweighted MMCD estimators.

`dets`
: Objective values for the final h-subsets.

`best_i`
: ID of subset with best objective.

`h_subset`
: Final h-subset of *raw* MMCD estimators.

`h_subset_reweighted`
: Final h-subset of *reweighted* MMCD estimators.

`iterations`
: Number of C-steps.

`dets_init_first`
: Objective values for the `nsamp` initial h-subsets after `max_iter_cstep_init` C-steps.

`subsets_first`
: Subsets created in subsampling procedure for large `n`.

`dets_init_second`
: Objective values of the 10 best initial subsets after executing C-steps until convergence.

References

Mayrhofer M, Radojičić U, Filzmoser P (2025). "Robust covariance estimation and explainable outlier detection for matrix-valued data." *Technometrics*, 1–15.

Rousseeuw P (1985). "Multivariate Estimation With High Breakdown Point." *Mathematical Statistics and Applications Vol. B*, 283-297. doi:10.1007/9789400954380_20.

Rousseeuw PJ, Driessen KV (1999). "A Fast Algorithm for the Minimum Covariance Determinant Estimator." *Technometrics*, **41**(3), 212-223. doi:10.1080/00401706.1999.10485670.

See Also

The `mmcd` algorithm uses the `cstep` and `mmle` functions.

Examples

```
n = 1000; p = 2; q = 3
mu = matrix(rep(0, p*q), nrow = p, ncol = q)
cov_row = matrix(c(1,0.5,0.5,1), nrow = p, ncol = p)
cov_col = matrix(c(3,2,1,2,3,2,1,2,3), nrow = q, ncol = q)
X <- rmatnorm(n = n, mu, cov_row, cov_col)
ind <- sample(1:n, 0.3*n)
X[,,ind] <- rmatnorm(n = length(ind), matrix(rep(10, p*q), nrow = p, ncol = q), cov_row, cov_col)
par_mmle <- mmle(X)
par_mmcd <- mmcd(X)
distances_mmle <- mmd(X, par_mmle$mu, par_mmle$cov_row, par_mmle$cov_col)
distances_mmcd <- mmd(X, par_mmcd$mu, par_mmcd$cov_row, par_mmcd$cov_col)
plot(distances_mmle, distances_mmcd)
abline(h = qchisq(0.99, p*q), lty = 2, col = "red")
abline(v = qchisq(0.99, p*q), lty = 2, col = "red")
```

---

mmd *Matrix Mahalanobis distance*

Description

Matrix Mahalanobis distance

Usage

```
mmd(X, mu, cov_row, cov_col, inverted = FALSE)
```

Arguments

X	a 3d array of dimension (p, q, n), containing n matrix-variate samples of p rows and q columns in each slice.
mu	a $p \times q$ matrix containing the means.
cov_row	a $p \times p$ positive-definite symmetric matrix specifying the rowwise covariance matrix
cov_col	a $q \times q$ positive-definite symmetric matrix specifying the columnwise covariance matrix
inverted	Logical. FALSE by default. If TRUE cov_row and cov_col are supposed to contain the inverted rowwise and columnwise covariance matrices, respectively.

Value

Squared Mahalanobis distance(s) of observation(s) in X.

Examples

```
n = 1000; p = 2; q = 3
mu = matrix(rep(0, p*q), nrow = p, ncol = q)
cov_row = matrix(c(1,0.5,0.5,1), nrow = p, ncol = p)
cov_col = matrix(c(3,2,1,2,3,2,1,2,3), nrow = q, ncol = q)
X <- rmatnorm(n = 1000, mu, cov_row, cov_col)
ind <- sample(1:n, 0.3*n)
X[,,ind] <- rmatnorm(n = length(ind), matrix(rep(10, p*q), nrow = p, ncol = q), cov_row, cov_col)
distances <- mmd(X, mu, cov_row, cov_col)
plot(distances)
abline(h = qchisq(0.99, p*q), lty = 2, col = "red")
```

---

mmle *Maximum Likelihood Estimation for Matrix Normal Distribtuion*

Description

mmle computes the Maximum Likelihood Estimators (MLEs) for the matrix normal distribution using the iterative flip-flop algorithm (Dutilleul 1999).

Usage

```
mmle(
  X,
  cov_row_init = NULL,
  cov_col_init = NULL,
  weight_mat_row = NULL,
```

```
  weight_mat_col = NULL,
  diag = "none",
  max_iter = 100L,
  lambda = 0,
  silent = FALSE,
  nthreads = 1L
)
```

Arguments

X	a 3d array of dimension (p, q, n), containing n matrix-variate samples of p rows and q columns in each slice.
cov_row_init	matrix. Initial cov_row $p \times p$ matrix, must be a positive definite symmetric matrix. Identity by default.
cov_col_init	matrix. Initial cov_col $p \times p$ matrix, must be a positive definite symmetric matrix. Identity by default.
weight_mat_row	$p \times p$ matrix. Weights applied to cov_row by elementwise multiplication, must be a positive definite symmetric matrix. NULL by default and not used.
weight_mat_col	$q \times q$ matrix. Weights applied to cov_col by elementwise multiplication, must be a positive definite symmetric matrix. NULL by default and not used.
diag	Character. If "none" (default) all entries of cov_row and cov_col are estimated. If either "both", "row", or "col" only the diagonal entries of the respective matrices are estimated.
max_iter	upper limit of iterations.
lambda	a smooting parameter for the rowwise and columnwise covariance matrices.
silent	Logical. If FALSE (default) warnings and errors are printed.
nthreads	Integer. If 1 (default), all computations are carried out sequentially. If larger then 1, matrix multiplication in the flip-flop algorithm is carried out in parallel using nthreads threads. Be aware of the overhead of parallelization for small matrices and or small sample sizes. If < 0, all possible threads are used.

Value

A list containing the following:

mu	Estimated $p \times q$ mean matrix.
cov_row	Estimated p times p rowwise covariance matrix.
cov_col	Estimated q times q columnwise covariance matrix.
cov_row_inv	Inverse of cov_row.
cov_col_inv	Inverse of cov_col.
norm	Frobenius norm of squared differences between covariance matrices in final iteration.
iterations	Number of iterations of the mmle procedure.

References

Dutilleul P (1999). "The mle algorithm for the matrix normal distribution." *Journal of Statistical Computation and Simulation*, **64**(2), 105-123. doi:10.1080/00949659908811970.

See Also

For robust parameter estimation use mmcd.

Examples

```
n = 1000; p = 2; q = 3
mu = matrix(rep(0, p*q), nrow = p, ncol = q)
cov_row = matrix(c(1,0.5,0.5,1), nrow = p, ncol = p)
cov_col = matrix(c(3,2,1,2,3,2,1,2,3), nrow = q, ncol = q)
X <- rmatnorm(n = 1000, mu, cov_row, cov_col)
par_mmle <- mmle(X)
```

---

n_subsets_mmcd

Number of subsets that are required to obtain at least one clean h-subset in the mmcd *function with probability* prob.

Description

Number of subsets that are required to obtain at least one clean h-subset in the mmcd function with probability prob.

Usage

```
n_subsets_mmcd(p, q, prob = 0.99, contamination = 0.5)
```

Arguments

p	number of rows.
q	number of columns.
prob	probability (default is 0.99).
contamination	level of contamination (default is 0.5).

Value

Number of subsets that are required to obtain at least one clean h-subset in the mmcd function with probability prob.

rmatnorm *Simulate from a Matrix Normal Distribution*

Description

Simulate from a Matrix Normal Distribution

Usage

```
rmatnorm(n, mu = NULL, cov_row, cov_col, sqrt = FALSE)
```

Arguments

n	the number of samples required.
mu	a $p \times q$ matrix containing the means.
cov_row	a $p \times p$ positive-definite symmetric matrix specifying the rowwise covariance matrix
cov_col	a $q \times q$ positive-definite symmetric matrix specifying the columnwise covariance matrix
sqrt	Logical. FALSE by default. If TRUE cov_row and cov_col are supposed to contain the square root of the rowwise and columnwise covariance matrices, respectively.

Value

If $n = 1$ a matrix with p rows and q columns, o otherwise a 3d array of dimensions (p, q, n) with a sample in each slice.

Examples

```
n = 1000; p = 2; q = 3
mu = matrix(rep(0, p*q), nrow = p, ncol = q)
cov_row = matrix(c(5,2,2,4), nrow = p, ncol = p)
cov_col = matrix(c(3,2,1,2,3,2,1,2,3), nrow = q, ncol = q)
X <- rmatnorm(n = 1000, mu, cov_row, cov_col)
X[,,9] #printing the 9th sample.
```

`weather` *Glacier weather data – Sonnblick observatory*

Description

Weather data from Austria's highest weather station, situated in the Austrian Central Alps on the glaciated mountain "Hoher Sonnblick", standing 3106 meters above sea level.

Usage

```
data(weather)
```

Format

An array of dimension (p, q, n), comprising $n = 136$ observations, each represented by a $p = 5$ times $q = 12$ dimensional matrix. Observed parameters are monthly averages of

- air pressure (AP)
- precipitation (P)
- sunshine hours (SH)
- temperature (T)
- proportion of solid precipitation (SP)

from 1891 to 2022.

Source

Datasource: GeoSphere Austria - https://data.hub.geosphere.at

Index

∗ **datasets**
darwin, 5
weather, 15

clean_prob_mmcd, 2
cstep, 3, *10*

darwin, 5

matrixShapley, 6
mmcd, *2*, *4*, 7, *13*
mmd, *6, 7*, 10
mmle, *10*, 11

n_subsets_mmcd, 13

rmatnorm, 14

weather, 15